FY316-07

乐风琴 | Rainbow metallophone with twin supports

技术资料 / TECHNICAL DATA SHEET

01 主视图 / MAIN VIEW



02 第二视图 / SECOND VIEW

未提供 / Not specified

03 俯视图 / TOP VIEW

未提供 / Not specified

材质说明 / MATERIAL SPECIFICATION

材料：铝管、镀锌钢管、不锈钢/镀锌金属、钢芯涤纶绳等。部件分配见明细表。

Materials: aluminium tube, galvanized steel tubes, stainless steel / galvanized metal, steel-core polyester rope and others. See the component schedule for allocation.

产品参数 / PRODUCT DATA

长度 Length	800 mm / 80 cm
宽度 Width	520 mm / 52 cm
总高 Total height	1000 mm / 100 cm
年龄 Age group	**待确认 / TBC**
人数 Users	**待确认 / TBC**
跌落高度 Free fall	**待确认 / TBC**
安全区 Safety zone	**待确认 / TBC**

材质状态 / MATERIAL STATUS

● 材质 / Materials　　仅列确认材质 / Confirmed only

材质确认不代表规格确认 / Material status excludes unspecified sizes

FY316-07

乐风琴 | Rainbow metallophone with twin supports

技术资料 / TECHNICAL DATA SHEET

部件与材质明细 / COMPONENT & MATERIAL SCHEDULE

编号	部件 / COMPONENT	材质 / MATERIAL	部件说明 / FUNCTION	状态 / STATUS
01	彩色音板 Coloured sounding bars	铝材。 Aluminium, as confirmed by the user.	数量、音阶和调音须厂家确认。 Count, scale and tuning require confirmation.	材质已确认 Confirmed
02	共鸣构件 Resonators	铝材。 Aluminium, as confirmed by the user.	下方共鸣构件按可见外观示意，尺寸及内部结构待确认。 Lower resonators follow visible appearance; dimensions and internal structure TBC.	材质已确认 Confirmed
03	支架与底座 Supports and bases	管式支架为镀锌钢管；非管底座为不锈钢/镀锌金属。 Tubular supports: galvanized steel; non-tubular base: stainless steel / galvanized metal.	立柱和底座如图所示。，锚固和基础规格待确认。 Posts and bases as illustrated; anchors and foundations TBC.	范围已确认 Range confirmed
04	连接及敲击配件 Joints and percussion accessories	敲击棒为铝管；连接绳为钢芯涤纶；连接五金为304不锈钢。 Mallets: user-specified aluminium tube; tethers: steel-core polyester; connection hardware: 304 stainless steel.	固定件及可见敲击配件；供货数量和连绳配置待确认。 Fixings and visible percussion accessories; supply counts and tether configuration TBC.	材质已确认 Confirmed

音阶、调音、发声件数量及安装需厂家复核。
Scale, tuning, sound-element counts and installation require verification.

未提供的厚度、管径、涂层、连接、承载及安全参数未作推定。
Unspecified thicknesses, tube sizes, finishes, connections, loads and safety parameters are not inferred.